

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: VINYL FINISH (ALL COLORS)
PRODUCT CODE: L770-MSDS

HMIS CODES: H F R P
0 0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CONTINENTAL COATINGS
ADDRESS: 10938 BEECH AVE, FONTANA, CALIFORNIA 92335
EMERGENCY PHONE: 714 355 1288 INFORMATION PHONE: 714 355 1200
DATE REVISED : 07-30-87 NAME OF PREPARER : ED KRISTY

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	N/A		
BUTYL ETHANOATE/BUTYL ACETATE	123-86-4	150 PPM	150 PPM		8.7 392F	45
*AROMATIC HYDROCARBON	108-88-3	200 PPM	150 PPM		N/A	12
*DI(2 ETHYLHEXYL) PHTHALATE			5 MG/M3		N/A	3
*2 BUTANONL/METHYL ETHYL KETONE	78-93-3	200 PPM			N/A	6

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 175 to 724 Deg F SPECIFIC GRAVITY (H2O=1): 1.1
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C. : 5.75 LB/GL (690 G/L)
MATERIAL V.O.C.: 5.75 LB/GL (690 G/L)
SOLUBILITY IN WATER: 18.4%
APPEARANCE AND ODOR: LIQUID - SOLVENT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 21 Deg F METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.0% UPPER: 15.0%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

LABORATORY EQUIPMENT SHOULD BE WORN TO AVOID INHALATION OF CONCENTRATED VAPORS. WATER SHOULD NOT BE USED EXCEPT AS A FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS

HANDLE AS A FLAMMABLE MATERIAL. VAPOR FORMS AN EXPLOSIVE MIXTURE WITH AIR BETWEEN THE UPPER AND LOWER EXPLOSIVE LIMITS.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE
CONDITIONS TO AVOID
HEAT AND FIRES

INCOMPATIBILITY (MATERIALS TO AVOID)

STRONG ALKALIES OR STRONG OXIDIZERS. THIS SOLVENT WILL DISSOLVE SOME PLASTICS, RUBBER MATERIALS OR COATINGS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

OVEREXPOSURE MAY CAUSE ANESTHESIA, HEADACHE, NAUSEA, OR DIZZINESS. BREATHING THE VAPOR MAY IRRITATE THE NOSE AND THROAT

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CONTACT WITH THE SKIN OR EYES MAY BE IRRITATING.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

HEALTH HAZARDS (ACUTE AND CHRONIC)

WARNING: AMOUNTS OF CHEMICALS OR SUBSTANCES KNOWN TO THE STATE OF CALIF. TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM MAY BE FOUND IN THIS PRODUCT. FOLLOW ALL APPLICABLE DIRECTIONS AND USE CARE WHEN HANDLING CHEMICAL AND PET ROLUEN PRODUCTS.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO
CALIFORNIA HEALTH AND SAFETY CODE SECTION 25249.6

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

REMOVE VICTIM TO FRESH AIR AND RESTORE BREATHING IF REQUIRED. CALL A PHYSICIAN FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. GET MEDICAL CARE IF DISCOMFORT PERSISTS. DO NOT INDUCE VOMITING UNLESS ADVISED TO DO SO BY A PHYSICIAN,

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION. PROVIDE ADEQUATE VENTILATION. FLUSH WITH WATER TO A TANK OR TO OPEN, WELL-VENTILATED AREA. ABSORB OR REMOVE TO CONTAINER AND DISPOSE OF PROPOSED PROPERLY IN CONFORMANCE WITH LOCAL REGULATIONS.

WASTE DISPOSAL METHOD

INCINERATE IF PERMITTED OR BURY IN A SANITARY LANDFILL. CONSULT A DISPOSAL EXPERT.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE FULL, PARTIAL, OR EMPTY DRUMS AWAY FROM HEAT OR FLAMES.

OTHER PRECAUTIONS

AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. KEEP AWAY FROM HEAT, SPARK AND OPEN FLAME. KEEP CONTAINER CLOSED.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

AIR PURPOSE CANISTER MASK OR AIR SUPPLIED MASK IF TLV EXCEEDED.

VENTILATION

PREFERABLE - MECHANICAL (GENERAL) - ACCEPTABLE.

PROTECTIVE GLOVES

ADVISABLE.

EYE PROTECTION

GOGGLES OR FACE SHIELD.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

EYE BATH AND SAFETY SHOWER.

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING WITH SOAP AND WATER.

===== SECTION IX - DISCLAIMER =====

DISCLAIMER

The opinions expressed herein are those of qualified C.C.Inc. and their suppliers. We believe that the information in is current as of the date of this MSDS. Since the use of the information and the conditions of use of the product is not within the control of C.C.Inc. it is the user's obligation to determine the safe use of it.